

# 8144 40% Bronze NFF

## Material Data Sheet

### Product Information

8144, 40% Bronze NFF

A non-oxidising 40% bronze filled PTFE compound.

### Features

Bronze is an alloy of copper and tin.

The non-oxidising alloy provides a consistent finished product appearance which is dark brown in colour.

Avoid use with Hydrofluoric Acid (HF) and strong alkalis.

Not suited to electrical applications.

Bronze is also attacked by certain chemicals.

### Benefits

Bronze filled PTFE provides:

- Excellent creep resistance
- Excellent wear resistance
- Strong thermal dissipation characteristics
- Strong electrical dissipation characteristics

### Typical Applications

- Piston rings
- Bushes – Bearings
- Linear bearings and guides
- Wear bands and strips
- Seals – Hydraulic systems

### Delivery Program

This product is sealed in two-layer plastic bags inside a rigid 25kg drum. It should be stored at 22 °C to 25 °C for 24 hours before processing.

This grade is available as:

- Non free flow
- Free flow available under product code 8444

### Physical Properties

Property	Value	Unit
Colour	Gold/Brown	
Bulk Density	710	g/l
Specific Gravity	3.10	g/cm <sup>3</sup>
Hardness	65 – 6	Shore D
Tensile Strength	7.21	MPa
Elongation	280	%
Shrinkage	2.5	%

